

Berwyndale Wallumbilla Pipeline

Receipt and Delivery Points

Receipt Points

Name	Location	Pressure (kPa)	Physical Capacity (GJ/Day)	Zone
			[see note 1]	[see note 2]
Berwyndale Receipt Point	The insulating flange gasket between the Pipeline and the QGC pipeline known as E06 at Berwyndale on the common fence line	Minimum: 9,600 Maximum: 13,500	164,000	BWP-RZ-02
Wallumbilla Receipt Point	The insulating flange gasket between the Pipeline and the SWQP	Minimum: 7,000 Maximum: 13,500	276,000	BWP-RZ-01

Delivery Points

Name	Location	Pressure (kPa)	Physical Capacity (GJ/Day)	Temperature (°C)	Zone
			[see note 1]		[see note 2]
Wallumbilla Delivery Point	The insulating flange gasket between the Pipeline and the SWQP	Minimum: 7,000 Maximum: 13,500	164,000	0-50	BWP-DZ-01

Silver Springs Delivery Point	The insulating flange gasket between the Pipeline and the Silver Springs Pipeline known as SSS1054 in Lot227 in Crown Plan WV1826	Minimum: 6,800 Maximum: 9,810	35,000	0-50	BWP-DZ-01
Berwyndale Delivery Point	The insulating flange gasket between the Pipeline and the QGC pipeline known as E06 at Berwyndale on the common fence line	Minimum: 7,000 Maximum: 13,500	276,000	0-50	BWP-DZ-02

Note 1: Hourly Physical Capacity unless otherwise stated is the Physical Capacity at the point divided by 24 and multiplied by the MHQ Factor for the Facility as set out in Schedule 10 of the Facility Specific Terms.

Note 2: Zones descriptions are accurate as at 1 July 2023, however are subject to change in accordance with the National Gas Rules. The zone information published in the AEMO Transportation Service Point Register prevails in the event of an inconsistency.